



**** NOTE ****

1. ROTATION : VIEWED FROM SHAFT END C.C.W
2. SHAFT POSITION : VERTICAL.
3. END PLAY : 1.0^{±0.05} mm
4. SCREW FASTENING TORQUE : 8Kg.cm MIN.
5. NAME PLATE POSITION : SURFACE "A"
6. AUDIBLE NOISE : 45dB MAX.
- 1) 30cm DISTANCE FROM SHAFT END.
- 2) SOUND LEVEL METER "A" SCALE.
- 3) AMBIENT NOISE : 25dB MAX.

NAME PLATE

| |
|----------------|
| IS-3230MUPA |
| AC230V 50Hz |
| SHING SHIN "B" |
| 00 00 00 |
| 00 00 00 |

YEAR MONTH DAY

"B" MARKING

| | |
|---------|-----------------|
| KOREA | MADE IN KOREA |
| CHINA | MADE IN CHINA |
| VIETNAM | MADE IN VIETNAM |

www.MuGul.com

UNIT : mm

| ITEM | PART DRAWN NO | PART NAME | MATERIAL | Q'TY | SIZE | REMARK |
|------|---------------|--------------------|--------------|------|-----------|--------|
| 9 | 5-30--00 | NAME PLATE | TERON SILVER | 1 | | |
| 8 | 5-56-4000-00 | HEX.NUT | MSWR10 | 2 | M4用 | FzY2 |
| 7 | 5-52-4046-90 | M/C SCREW(S/W) | MSWR10 | 2 | PH⊕M4*L46 | FzY2 |
| 6 | 5-21-0007-00 | SPRING ADH. WASHER | SK-5 | 1 | 625用 | BLUING |
| 5 | 3-31-0189-00 | STEEL WASHER | SPC-1 | 1 | 625用 | T=0.5 |
| 4 | 3-20-0375-00 | BRACKET "REAR" | ADC12 | 1 | | |
| 3 | 3-20-0376-00 | BRACKET "FRONT" | ADC12 | 1 | | |
| 2 | 2-10--00 | STATOR ASS'Y | S-60 | 1 | | |
| 1 | 2-30--00 | ROTOR ASS'Y | S-60/AL | 1 | | |

| | | | | | | | | |
|-------------|----------|---------|----------------|-------|-------|-----|-----------|----------|
| 날 짜 | DATE | 시 영 | SIGN | 변 경 | NOTE | 내 용 | 변 경 이 유 | REVISION |
| 재 질 | MATERIAL | 표 면 처 리 | SURFACE FINISH | 척 도 | SCALE | 적 차 | TOLERANCE | |
| 제 도 | DRAWN | 실 계 | CHECK | 승 인 | APPR. | 도 명 | NAME | |
| DATE | DESIGN | DESIGN | CHECK | APPR. | NAME | | | |
| MOTOR ASS'Y | | | | | | | | |
| IS-3230MUPA | | | | | | | | |
| 작성 일 | DATE | 도 번 | DWG NO. | 1-03- | 00 | | | |
| '10.06.28 | | | | | | | | |